

VERY IMPORTANT NOTE

This Revotec cooling kit has been engineered to provide perfect cooling for your XK120. However it is essential that the other components in the cooling system are operating correctly.

The following must be checked:

1. The radiator has a normal life expectancy of approximately 8-9 years, after this time it should be thoroughly assessed and any signs of deterioration, such as furring up internally or distortion, a replacement is recommended.
2. The radiator fins must be clear of all debris such as mud and leaves.
3. The system must be filled with the correct coolant.
4. The water pump and thermostat must be operating correctly.

1. Disconnect the battery earth terminal, drain water system and remove the top hose.
2. Mount the electric fan to the front of the radiator using the FPK01 fan pull through kit, by applying the self-adhesive rubber pads to the underside of the fan under the mounting lug, position the fan on the radiator core, feed the pins through the fan mounting lugs, through the rubber pads, then through the radiator core, on the other side of the radiator core slide on the foam pads onto the 4 exposed pins, slide the plastic ratchet buttons onto the 4 exposed pins and pull tight, cut off the excess.
3. Position the fan controller in a suitable place in the top hose, refill the water system and follow electronic fan controller instructions for wiring information, we recommend a 20a blade fuse for the power supply.
4. Reconnect the battery earth terminal and follow the electronic fan controller instructions for setup information.